



FLATRACK NOMINAL SPECS*		
DIMENSION	DESCRIPTION	40' SUPERRACK V4.1
L1	INSIDE LENGTH BETWEEN ENDWALL TOP RAILS	11924mm
W2	INSIDE WIDTH BETWEEN POSTS	2110mm
H3 (H3 _{Min} ~ H3 _{Max})	INSIDE HEIGHT BETWEEN TOP CORNERCASTING AND FLOOR (H3 _{Min} : INNER POSTS FULLY RETRACTED) (H3 _{Max} : INNER POSTS FULLY EXTENDED)	Min: 2264mm Max: 3483mm
H4	HEIGHT BETWEEN FLOOR AND BOTTOM CASTING	632mm
H5	HEIGHT WHEN END WALL FLUSH FOLDED	648mm
L6	INSIDE LENGTH BETWEEN POSTS REINFORCEMENTS	11615mm
W7	DECK WIDTH	2374mm
L8	EXTERNAL LENGTH	12192mm
H9 (H9 _{Min} ~ H9 _{Max})	EXTERNAL HEIGHT (H9 _{Min} : INNER POSTS FULLY RETRACTED) (H9 _{Max} : INNER POSTS FULLY EXTENDED)	Min: 2896mm Max: 4115mm
W10	EXTERNAL WIDTH	2438mm
W11	WIDTH BETWEEN STANCHIONS	2204mm
H12	CAMBER AT CENTER BEFORE LOADING	50mm
	MAXIMUM GROSS WEIGHT	50,000KGS
	TARE WEIGHT	6,000KGS
	MAXIMUM PAYLOAD	44,000KGS
	END LASHING POINTS (QUANTITY)	4
	SIDE LASHING POINTS (QUANTITY)	19
	SIDE STAKE POCKETS (QUANTITY)	6
	FORKLIFT POCKETS	YES (EMPTY LIFT ONLY)
	STACKABLE QUANTITY	4 PER 8'6"

* The figures on the above table are for user's guidance only.