


---

Item no.: 282-870  
Product description: DISCONNECT TERMINAL BLOCK FOR TEST PURPOSES  
with touch-proof test plugs FOR TEST PLUG 4 MM / 0.157 IN Ø  
EXAMPLE FOR CURRENT TRANSFORMER CIRCUITS  
DISCONNECT LINK ORANGE

---



Produkt kann von Bild abweichen / product may differ

Packing unit 20 pieces

RoHS compliant

Product group	1 (Rail Mounted Terminal Blocks)
Cross section [mm <sup>2</sup> ]	0.2 - 6 mm <sup>2</sup>
Cross section [AWG]	24 - 10 AWG
Connection method	CAGE CLAMP® CONNECTION
Measured voltage EN	500 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	30 A
Weight	48.221 g
Color	gray
Wiring type	Front-entry
No. of connection Points	3
No. of potentials	2
Height	75 mm
Height	2.95 in
Width	8 mm
Width	0.315 in

Depth	122 mm
Depth	4.8 in
Strip length from	12 mm
Strip length to	13 mm
Strip length	0.49 in
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
282-870	ABS	05-HG476175/3-PDA	500	30	6
282-870	BV	07436/Co	500	30	6
282-870	CCA	NL5448	500	30	6
282-870	CSA	154112-1505033	300	5	24-10
282-870	DNV	E-10423	500	30	6
282-870	GL	17295-00HH	500	30	6
282-870	KEMA	2036290.01	500	30	6
282-870	LR	91/20112(E6)	500	30	6
282-870	PRS	TE/1718/880590/08	500	30	6
282-870	RMR	11130002	500	30	6
282-870	UR	E45172	600	30	24-10

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected