# 16" and 20" Composite Slickline Floor Sheave



The Wireline Technologies, Inc. 16" and 20" Slickline Sheave feature a lightweight composite wheel, high strength aluminium and stainless steel structural components, and a simple side loading system that provides easy line placement. Incorporation of cable shrouds above the wheel prevents the line from "jumping sheave." Side locking design provides increased durability and ease of use.



## **Dimensions & Weights**

16":	(W) 10.16 cm, 4 in (H) 66.04 cm, 26 in
	(Weight) 9 kg, 20 lbs
20":	(W) 10.16 cm, 4 in (H) 76.20 cm, 30 in
	(Weight) 10.5 kg, 23 lbs

#### **Specifications**

- SWL- 6,000 lbs. (3,000 lbs. line)
- Proof test load- 12,000 lbs. (6,000 lbs. Line)
- Standard line sizes- .092"-.108" & .108"- 125" (Custom grooving is available)

#### **Features & Benefits**

- Side loading system for ease of use
- Cable shrouds reduce "line jumping"
- Composite wheel is less abrasive to expensive lines
- One year manufacturers warranty
- Fully certified (Certificate supplied)
- Solid wheel and available handguard for added safety









## Floorstand

- Provides support for your WTI Sheave
  One sided design allows the line to be
- loaded/unloaded while attached
- Sizes available for the 16" and 20" as well as the 25 and 30" sheaves
- Powder coated to protect against corrosion

PART NUMBER L-840998

## Handguard / Bushing System

- Protects operator's hands and clothing from being drawn into sheave
- Should be used wherever a running line can be touched by an operator
- Patented design allows the line to be loaded after attachment
- Can be used to keep the sheave upright during slack line conditions

### PART NUMBER L-840999

#### Line Wiper

- Helps maintain a clean running line, reducing maintenance time
- Easily attached to sheave and adjustable to fit any line size
- Made from anodized aluminium to protect against corrosion

#### PART NUMBER L-8601028884

#### **Rig-Up Yoke**

- Provides an alternative place to attach a "tugger line"
- Can be used to stabilize top mounted (hanging) sheaves
- Made from stainless steel to resist corrosion

### PART NUMBER L-8601019096

#### PART NUMBERS

Part Number	Sheave Size	Wire	Clevis Type
L-8601017000D108	16"	0.092"-0.108"	Eye
L-8601017000D125	16"	0.125"	Eye
L-8601019057D108	16"	0.092"-0.108"	Hook
L-8601019057D125	16"	0.125"	Hook
L-8601020421D125	20"	0.125"	Eye
L-8601020422D125	20"	0.125"	Hook
L-8601020422D108	20"	0.092"-0.108"	Hook
L-8601024736D156	20"	0.140"-0.160"	Hook
L-8601029328D156	20"	0.140"-0.160"	Eye

Note: For North America inquiries please contact Wireline Technologies Inc directly, for all other areas please contact your local NOV ASEP Elmar sales office.



99