

















Card No	Description	Photo
CO-267	18 3/4" seal assembly: type SS 15, 15,000 psi for all hangers 13 3/8" and smaller, weight set dual metal to metal seals, includes outer lock ring, H2S service. PART: 2-401845-02; Reference sales order item 34	 
CO-191	22" x 16" big bore II seal assembly: weight set metal to metal, 6,500 psi rated, H2S service PART: 2-403134-01	 
CO-262	18" seal assembly, type SS 10/15/20, API 6A, V, AA, PSL-2, for use with 18" supplemental hanger, for use with big bore II / big bore II-h wellhead system. PART: 2-403132-02; reference sales order item 21	 
CO-265	16" seal assembly: type ss-10/ss-15, 6,500 psi, V, DD, PSL-3, H2S service, for 16" supplemental hanger, for external lock-ring conversions only, for use with big bore II wellhead system. PART: 2-411873-02, reference sales order item 26	 



Card No	Description	Photo
CO-275	18-3/4" stabilizer sub for big bore wear sleeves. 7-5/8" API Reg. box up x pin down. PART: 2-403666-02	 
CO-272	18-3/4" x 13-3/8" adapter sleeve: type ss 15, run with 6-5/8" tool, joint bit sub and 13-3/8" wear bushing, "J" lug style, for use with big bore or standard bore welhead systems. PART: 2-403961-02	 
CO-271	18-3/4" x 13-3/8" selectable wear bushing/sleeve: type ss 15, to be run with multiple running and retrieving subs (12.25" dia.), bit runnable selective retrieval, upper profile for BOP test tool adapter, big bore and standard bore welhead systems. Rated for high temperature/high load. H2S service, PART: 2-404122-02; Reference sales order item 46	
CO-257	36" x 28" positive stop casing hanger, 28" OD x .750" wall BWP, max. OD. 30.510", min. ID. 26.500", elevator shoulder, solid landing shoulder with split lock ring, PART: 2-404182-04; reference sales order item 11	






Card No	Description	Photo
CO-270	18-3/4" selectable J-type wear bushing running and retrieving tool, type ss-15, 6-5/8" API F.H. box up with bore back relief by pin with relief groove. 9.980" max. O.D., extended wear area. PART: 2-405222-02	
CO-025	18 3/4" x 13 3/8" wear bushing, type SS 15: protects ID of housing and hanger. Run and retrieved with multi purpose tool. Complete with load transfer grooves. PART: 2-400950-02	



Card No	Description	Photo
CO-020	18 3/4" x 9 5/8" casing hanger, 15,000 psi, type SS 15, blank box down, profile for sealing and locking down weight set metal to metal seal assembly. Hanger min. ID 8.535". PART: 2-414791-02	
CO-029	Annulus outlet sub, type SS-15, 36" x 2.000" wall BWP up and down with eight (8) 4" - NPT outlets, 30.72" min. ID PART: 2-414521-02	
CO-264	22" x 16" big bore II positive stop casing hanger. Type ss-10/15, 16", 96 lb/ft, Hydril 513 Box down, 6,500 psi rated, 14.827" min I.D. V, AA, PSL-3, PART: 2-404720-01; Reference sales order item 24	



Card No	Description	Photo
CO-263	22" x 16" big bore II casing hanger adapter, 22" x 1.000" wall BWP down x 22" x 1.000" wall BWP up for 16" "no-go" style supplemental hanger with 18.375" min I.D. (weight set), with OD lock ring profile. PART: 2-413627-02; reference sales order item 22	
CO-273	18-3/4" X 14-1/2" wear sleeve, big bore system, "J" type. PART: 2-403663-02	
CO-026	18 3/4" x 9 5/8" wear bushing, high temp., high load, 8.822" min. ID PART: 4-400547-02	
CO-274	18-3/4" X 14-1/2" wear sleeve bit sub. 7-5/8" API reg. Box up x pin down. PART: 2-403665-02	