

CertainTeed

Flintlastic® GMS, GTA, SA

Colors that complement the most popular
CertainTeed® shingles



Colonial Slate

Weathered Wood

Heather Blend

Resawn Shake

White

Moiré Black

Burnt Sienna

CoolStar™

CertainTeed
SAINT-GOBAIN



Now you can color coordinate a low slope roof to an adjacent shingle roof. Flintlastic® GMS, GTA and SA Cap are available for three distinct methods of application.

GMS (Mop)

- SBS modified bitumen for hot asphalt or approved cold adhesive application
- Meets or exceeds ASTM D6164, Type 1
- Roll coverage: 1 square
- Thickness: 3.7 mm
- Reinforcement: polyester mat
- Roll weight: 93 lbs.
- Rolls per pallet: 20

GTA (Torch)

- APP modified bitumen for torch application
- Meets or exceeds ASTM D6222, Type 1
- Roll coverage: 1 square
- Thickness: 4.0 mm
- Reinforcement: polyester mat
- Roll weight: 103 lbs.
- Rolls per pallet: 20

SA Cap (Self-Adhering)

- SBS modified bitumen
- No torches or hot asphalt needed
- Removable release film
- Meets or exceeds ASTM D6164, Type 1
- Roll coverage: 1 square
- Thickness: 4.0 mm
- Reinforcement: polyester mat
- Roll weight: 95 lbs.
- Rolls per pallet: 20



Flintlastic colors are also available in special runs for FR Cap, FR-P, GTS and SA Cap FR.

CertainTeed Flintlastic roofing products are intended for use by professional roofing contractors only. It is the responsibility of the installer to follow all appropriate safety precautions in conjunction with the installation of any CertainTeed roofing product.



ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • WINDOWS • DECKING • RAILING • FENCE
INSULATION • GYPSUM • CEILINGS • FOUNDATIONS • PIPE

www.certainteed.com <http://blog.certainteed.com>

CertainTeed Corporation
20 Moores Road
Malvern, PA 19355

Professional: 800-233-8990
Consumer: 800-782-8777

© 1/16 CertainTeed Corporation, Printed in U.S.A.
Code No. COMM-086

